

Tap-offs with F-connections, frequency range up to 2400 MHz

Type	AFC 1021 S	AFC 1521 S	AFC 2021 S	AFC 2521 S
Order No.	947 566-002	947 567-002	947 622-002	947 660-002



- Die-cast housing
- Two splitters can be mounted on top of each other using the spacer supplied
- For 1 SAT-IF distribution in buildings
- Remote feed via master, max. 1 A/24 V DC
- Conforms to EN 50083-2



Throughpass attenuation	Frequency range MHz 5-40	4.5 dB	3 dB	2 dB	1.5 dB
	Frequency range MHz 40-1000	3.5 dB	3 dB	2 dB	1.5 dB
	Frequency range GHz 1-2.4	4.5 dB	4 dB	3 dB	2.5 dB
Tap-off attenuation	Frequency range MHz 5-40	11 dB	15 dB	20 dB	25 dB
	Frequency range MHz 40-1000	11 dB	15 dB	20 dB	25 dB
	Frequency range GHz 1-2.4	11 dB	15 dB	20 dB	25 dB
Coupling attenuation	Frequency range MHz 5 - 40	35 dB	40 dB	45 dB	20 dB
	Frequency range MHz 40-1000	25 dB	35 dB	35 dB	20 dB
	Frequency range GHz 1-2.4	25 -20 dB	30 -25 dB	30 dB	20 dB
Directional attenuation	Frequency range MHz 5-40	18 dB	23 dB	25 dB	30 dB
	Frequency range MHz 40-1000	18 dB	20 dB	22 dB	25 dB
	Frequency range GHz 1-2.4	17 dB	20 dB	22 dB	25 dB
Technical data	Dimensions Ø	75x53x16 mm	75x53x16 mm	75x53x16 mm	75x53x16 mm
	Drawing				