

Distribution boxes with F connections, frequency range up to 1000 MHz

Type	VFC 0421	VFC 0631	VFC 0741	VFC 1061	VFC 1281
Order No.	947355-101	947356-101	947357-101	981000-108	981000-109



- Die-cast housing
- For CATV indoor distribution
- For F-connections with inner conductor \emptyset :
min. 0.5 mm
max. 1.2 mm
- Suitable for return path
- Inner conductor isolated capacitively
- Surface mounted
- Meets EN 50083-2



Distribution attenuation 1+2 Frequency range MHz 5-40 Frequency range MHz 40-1000	3.5 dB 3.9 -4.4 dB	5.5 dB 5.8 -6.8 dB	7.2 dB 7.5 -8.2 dB	10.7 dB 10.7 - 12.0 dB	12.3 dB 12.3 - 13.2 dB
Distribution attenuation 3 Frequency range MHz 5-40 Frequency range MHz 40-1000	- -	5.5 dB 5.8 -6.8 dB	7.2 dB 7.5 -8.2 dB	10.7 dB 10.7 - 12.0 dB	12.3 dB 12.3 - 13.2 dB
Distribution attenuation 4 Frequency range MHz 5-40 Frequency range MHz 40-1000	- -	- -	7.2 dB 7.5 -8.2 dB	10.7 dB 10.7 - 12.0 dB	12.3 dB 12.3 - 13.2 dB
Distribution attenuation 5+6 Frequency range MHz 5-40 Frequency range MHz 40-1000				10.7 dB 10.7 - 12.0 dB	12.3 dB 12.3 - 13.2 dB
Distribution attenuation 7+8 Frequency range MHz 5-40 Frequency range MHz 40-1000					12.3 dB 12.3 - 13.2 dB
Coupling attenuation Frequency range MHz 5 - 40 Frequency range MHz 40-1000	24 dB 25 -20 dB	20 dB 25 -22 dB	22 dB 24 -20 dB	12 dB 20 dB	14 dB 20 dB
Technical data Dimensions \emptyset Drawing	50x51x24 mm 	75x51x24 mm 	75x51x24 mm 	135x60x4 1 mm 	135x60x4 1 mm