

TechniCrypt CX Pro

Professional CI module with CONAX encryption system



MAIN HARDWARE FEATURES:

CI-Interface	EN 50221, PC-Card-Standard
2.0	vol. 2, 3, 4 compliant
1x Smartcard Reader	ISO 7816-3 compliant
Flash - memory	2 MByte
Ram - memory	8 MByte
Transportstream-I/O	ISO 13818-1 compliant
Power supply:	5V / 3.3V DC-DC-conversion
Power consumption	< 600 mW
Input voltage range	DC 5V according to CI-Standard
Dimensions (WxDxH):	85.6 mm x 54 mm x 4 mm
Package type	Type 2 PC Card Package
Housing:	metal chassis according to PC Card-Standard 2.0
Main Software features:	
CAS - System	CONAX CAS
	Multiservice support
Firmware Update	OTA download of CONAX signed images
OSD languages:	German, English

The TechniSat TechniCrypt CX Pro has been especially developed to be used in Headend-Systems. This module enables the encryption of a complete transponder network. Therefore it is possible that a complete satellite transponder with only one module and one SmartCard can be encrypted and conditioned through the Headend-Station. The TechniCrypt CX Pro is the consistent advancement of the approved TechniSat CI-Module series by a professional conditional access module.

TechniSat[®]
DIGITAL

www.technisat.com

TechniSat Digital S.A., MediaCenter Betzdorf · L-6832 Betzdorf

